

PRODUCT OVERVIEW 08/2018



CONTENTS

Colour Systems

A3 Multifunctional Systems	page 3
A4 Multifunctional Systems	page 5
A4 Print Systems	page 8

b/w Systems

A3 Multifunctional Systems	page 9
A4 Multifunctional Systems	page 13
A3 Print System	page 17
A4 Print Systems	page 18

A3 MULTIFUNCTIONAL SYSTEMS



		P-C2480i MFP	2506ci	3206ci	4006ci
Copy	Copy speed	24 A4 / 12 A3 pages/min in colour and b/w	25 A4 / 12 A3 pages/min in colour and b/w	32 A4 / 16 A3 pages/min in colour and b/w	40 A4 / 20 A3 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	600 (500 + 100 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	Optional paper feed	1 or 2 x 500 sheets	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	Paper capacity, max	1,600 sheets	7,150 sheets	7,150 sheets	7,150 sheets
	Paper format	A6R-A3	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+
	Original feeder	Standard	Option: DP-7100, DP-7110 or DP-7120	Option: DP-7100, DP-7110 or DP-7120	Option: DP-7100 or DP-7110
	Duplex	Standard	Standard	Standard	Standard
	System memory	1.5 GB (max 3 GB)	4 GB RAM, 32 GB SSD/optional: 320 GB HDD	4 GB RAM, 32 GB SSD/optional: 320 GB HDD	4 GB RAM, 8 GB SSD/320 GB HDD
Zoom	25%-400%	25%-400%	25%-400%	25%-400%	
Cabinet	Option: no. 62	Option: no. 76	Option: no. 76	Option: no. 76	
Print	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8
	Emulations	PCL6 (5c, XL), KPD L 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6 (5c, XL), KPD L 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6 (5c, XL), KPD L 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6 (5c, XL), KPD L 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
Scan	Scan type	CIS colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
Fax	Originals	max A3	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	1,000/2,000	1,000/2,000	1,000/2,000

A3 MULTIFUNCTIONAL SYSTEMS



		5006ci	6006ci	7006ci	8006ci
Copy	Copy speed	50 A4 / 25 A3 pages/min in colour and b/w	55/60 A4 / 27/30 A3 pages/min in colour and b/w	65/70 A4 / 32/35 A3 pages/min in colour and b/w	70/80 A4 / 35/40 A3 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	Optional paper feed	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	Paper capacity, max	7,150 sheets	7,150 sheets	7,650 sheets	7,650 sheets
	Paper format	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-A3+	A6R-A3+
	Original feeder	Option: DP-7100 or DP-7110	Option: DP-7100 or DP-7110	Standard	Standard
	Duplex	Standard	Standard	Standard	Standard
	System memory	4 GB RAM, 8 GB SSD/320 GB HDD	4 GB RAM, 8 GB SSD/320 GB HDD	4.5 GB RAM, 8 GB SSD/320 GB HDD	4.5 GB RAM, 8 GB SSD/320 GB HDD
Zoom	25%-400%	25%-400%	25%-400%	25%-400%	
Cabinet	Option: no. 76	Option: no. 76	--	--	
Print	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8
	Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIc
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
Scan	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
Fax	Originals	max A3	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	1,000/2,000	1,000/2,000	1,000/2,000	1,000/2,000

A4 MULTIFUNCTIONAL SYSTEMS



		301ci	350ci	400ci
Copy	Copy speed	30 A4 pages/min. in colour and b/w	35 A4 pages/min. in colour and b/w	40 A4 pages/min. in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	Optional paper feed	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets	1 x 500 + 2 x 500 or 1 x 2,000 sheets
	Paper capacity, max	3,100 sheets	3,100 sheets	3,100 sheets
	Paper format	A6R-A4	A6R-A4	A6R-A4
	Original feeder	Standard	Option: DP-5100 or DP-5110	Option: DP-5100 or DP-5110
	Duplex	Standard	Standard	Standard
	System memory	1 GB RAM (max. 2 GB RAM)	2 GB RAM, 8 GB SSD/optional: 320 GB HDD	2 GB RAM, 320 GB HDD
Zoom	25%-400%	25%-400%	25%-400%	
Cabinet	Option: high Nr. 74, low Nr. 75	Option: high Nr. 74, low Nr. 75	Option: high Nr. 74, low Nr. 75	
Print	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (2)	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (3)	USB 2.0 (opt.), 10/100/1000BaseTX, USB host (3)
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, OpenXPS	
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows XP, Vista, 7/8/8.1/10, Server 2003/2008 R2/2012 R2,
Scan	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP
Fax	Originals	max A4	max A4	max A4
	Modem speed	33,6 kbps	33,6 kbps	33,6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	1,000/2,000	1,000/2,000

A4 MULTIFUNCTIONAL SYSTEMS



P-C2155w MFP



P-C2655w MFP



356ci

Copy	Copy speed	21 A4 pages/min in colour and b/w	26 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	300 (1 x 250 + 50 sheets)	300 (1 x 250 + 50 sheets)	350 (1 x 250 + 100 sheets)
	Optional paper feed	1 x 250 sheets	1 x 250 sheets	3 x 500 sheets
Print	Paper capacity, max	550 sheets	550 sheets	1,850 sheets
	Paper format	A6R-A4	A6R-A4	A6R-A4
	Original feeder	Standard	Standard (Duplex Scan)	Standard (Duplex Scan)
	Duplex	Standard	Standard	Standard
	System memory	512 MB RAM (max 1,536 MB)	512 MB RAM (max 1,536 MB)	1,024 MB RAM (max 3,072 MB RAM)
	Zoom	25%–400%	25%–400%	25%–400%
	Cabinet	Option: no. 77	Option: no. 77	Option: high no. 72, low no. 73
	Type	Integrated within the system	Integrated within the system	Integrated within the system
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi	USB 2.0, 10/100/1000BaseTX, USB host (2)	
Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	
	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
Scan	Scan type	CIS colour and b/w	CIS colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP
Fax	Originals	max A4	max A4	max A4
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	22/100	100/200	100/200

A4 MULTIFUNCTIONAL SYSTEMS



		P-C3062i MFP	P-C3066i MFP	P-C3562i MFP	P-C3566i MFP
Copy	Copy speed	30 A4 pages/min in colour and b/w	30 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w	35 A4 pages/min in colour and b/w
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	Optional paper feed	3 x 500 sheets	3 x 500 sheets	3 x 500 sheets	3 x 500 sheets
	Paper capacity, max	1,850 sheets	1,850 sheets	1,850 sheets	1,850 sheets
	Paper format	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	Original feeder	Standard	Standard	Standard (Duplex Scan)	Standard (Duplex Scan)
	Duplex	Standard	Standard	Standard	Standard
	System memory	1,024 MB RAM (max 3,072 MB RAM)	1,024 MB RAM (max 3,072 MB RAM)	1,024 MB RAM (max 3,072 MB RAM)	1,024 MB RAM (max 3,072 MB RAM)
Zoom	25%–400%	25%–400%	25%–400%	25%–400%	
Cabinet	Option: high no. 72, low no. 73	Option: high no. 72, low no. 73	Option: high no. 72, low no. 73	Option: high no. 72, low no. 73	
Print	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)	USB 2.0, 10/100/1000BaseTX, USB host (2)
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS	
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
Scan	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
Fax	Originals	--	max A4	--	max A4
	Modem speed	--	33.6 kbps	--	33.6 kbps
	Compression method	--	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	100/200	--	100/200

A4 PRINT SYSTEMS



P-C2650DW

Print format	A6R-A4
Print speed	26 A4 pages/min in colour and b/w
Print resolution	600 x 600 dpi, 9,600 x 600 dpi level, 1,200 x 1,200 dpi (reduced speed)
Standard paper feed	300 (1 x 250 + 50 sheets)
Optional paper feed	1 x 250 sheets
Duplex	Standard
Processor	Cortex-A9 / 800 MHz
Print memory	512 MB (max 512 MB)
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host, SD slot, Wi-Fi
Network card optional	--
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS, Open XPS



P-C3062DN

Print format	A6R-A4
Print speed	30 A4 pages/min in colour and b/w
Print resolution	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
Standard paper feed	600 (1 x 500 + 100 sheets)
Optional paper feed	3 x 500 sheets
Duplex	Standard
Processor	ARM Cortex-A9 dual core/1.2 GHz
Print memory	1,024 MB (max 1,024 MB)
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2)
Network card optional	IB-50 Gigabit Ethernet, IB-36/IB-51 WLAN card
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS



P-C3562DN

Print format	A6R-A4
Print speed	35 A4 pages/min in colour and b/w
Print resolution	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
Standard paper feed	600 (1 x 500 + 100 sheets)
Optional paper feed	3 x 500 sheets
Duplex	Standard
Processor	ARM Cortex-A9 dual core/1.2 GHz
Print memory	1,024 MB (max 3,072 MB)
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2)
Network card optional	IB-50 Gigabit Ethernet, IB-36/IB-51 WLAN card
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS

P-C4072DN

Print format	A6R-A4
Print speed	40 A4 pages/min in colour and b/w
Print resolution	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
Standard paper feed	600 (1 x 500 + 100 sheets)
Optional paper feed	3 x 500 sheets
Duplex	Standard
Processor	ARM Cortex-A9 dual core/1.2 GHz
Print memory	1,024 MB (max 3,072 MB)
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2)
Network card optional	IB-50 Gigabit Ethernet, IB-36/IB-51 WLAN card
Emulations	PCL6 (5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS

A3 MULTIFUNCTIONAL SYSTEMS



1855

Copy	Copy speed	18 A4 / 8 A3 pages/min
	Copy resolution	600 x 600 dpi
	Greyscales	256
	Standard paper feed	400 (300 + 100 sheets)
	Optional paper feed	3 x 300 sheets
	Paper capacity, max	1,300 sheets
	Paper format	A6R-A3
	Original feeder	Option: DP-480
	Duplex	Option: DU-480
	System memory	256 MB
Zoom	25%–400%	
Cabinet	Option: high no. 68, low no. 69	
Print	Type	Integrated within the system
	Interfaces	USB 2.0
	Operating systems	Windows 7/8/8.1/10, Mac ex OS 10.5
Emulations	GDI	
Network	Interfaces	--
	Network protocols	--
	Operating systems	--
Scan	Scan type	CIS colour and b/w
	Scan resolution	200, 300, 400 (only b/w), 600 (only b/w) dpi
	Interfaces	USB 2.0
	Network protocols	--
Fax	Originals	--
	Modem speed	--
	Compression method	--
	One-touch dial/abbr. dial	--

2256

Copy speed	22 A4 / 10 A3 pages/min
Copy resolution	600 x 600 dpi
Greyscales	256
Standard paper feed	400 (300 + 100 sheets)
Optional paper feed	3 x 300 sheets
Paper capacity, max	1,300 sheets
Paper format	A6R-A3
Original feeder	Option: DP-480
Duplex	Option: DU-480
System memory	256 MB
Zoom	25%–400%
Cabinet	Option: high no. 68, low no. 69
Type	Integrated within the system
Interfaces	USB 2.0
Operating systems	Windows 7/8/8.1/10, Mac ex OS 10.5
Emulations	GDI
Interfaces	(optional)
Network protocols	TCP/IP
Operating systems	Windows 7/8/8.1/10
Scan type	CIS colour and b/w
Scan resolution	200, 300, 400 (only b/w), 600 (only b/w) dpi
Interfaces	USB 2.0
Network protocols	--
Originals	max A3
Modem speed	33.6 kbps
Compression method	MMR, MR, MH
One-touch dial/abbr. dial	32/120



P-2540i MFP

Copy speed	25 A4 / 12 A3 pages/min
Copy resolution	600 x 600 dpi
Greyscales	256
Standard paper feed	600 (1 x 500 + 100 sheets)
Optional paper feed	1 or 2 x 500 sheets
Paper capacity, max	1,600 sheets
Paper format	A6R-A3
Original feeder	Standard
Duplex	Standard
System memory	1 GB (max 3 GB)
Zoom	25%–400%
Cabinet	Option: no. 62
Type	Integrated within the system
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi
Operating systems	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016, Novell Netware, Linux, Mac ex OS 10.5
Emulations	PCL6 (5c, XL), KPDLL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe, PDF 1.7
Interfaces	10/100/1000BaseTX
Network protocols	TCP/IP, Net BEUI
Operating systems	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016
Scan type	CIS colour and b/w
Scan resolution	200, 300, 400, 600 dpi
Interfaces	10/100/1000BaseTX, USB 2.0
Network protocols	TCP/IP
Originals	max A3
Modem speed	33.6 kbps
Compression method	JBIG, MMR, MR, MH
One-touch dial/abbr. dial	100/200

A3 MULTIFUNCTIONAL SYSTEMS



		3262i	4062i
Copy	Copy speed	32 A4 / 17 A3 pages/min	40 A4 / 21 A3 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256
	Standard paper feed	1,100 (2 x 500 + 100 sheets)	1,100 (2 x 500 + 100 sheets)
	Optional paper feed	2 x 500 sheets or 2 x 1,500 sheets	2 x 500 sheets or 2 x 1,500 sheets
	Paper capacity, max	4,100 sheets	4,100 sheets
	Paper format	A6R-A3	A6R-A3
	Original feeder	Option: DP-7100, DP-7110 or DP-7120	Option: DP-7100, DP-7110 or DP-7120
	Duplex	Standard	Standard
	System memory	2 GB RAM, 32 GB SSD / optional: 320 GB HDD	2 GB RAM, 8 GB SSD/320 GB HDD
Zoom	25%-400%	25%-400%	
Cabinet	Option: no. 70	Option: no. 70	
Print	Type	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8
	Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
Scan	Scan type	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP
Fax	Originals	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	1,000/2,000	1,000/2,000

A3 MULTIFUNCTIONAL SYSTEMS



		4056i	5056i	6065i
Copy	Copy speed	40 A4 / 20 A3 pages/min	50 A4 / 25 A3 pages/min	60 A4 / 30 A3 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)	1,150 (2 x 500 + 150 sheets)
	Optional paper feed	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	Paper capacity, max	7,150 sheets	7,150 sheets	7,150 sheets
	Paper format	A6R-SRA3/A3+	A6R-SRA3/A3+	A6R-SRA3/A3+
	Original feeder	Option: DP-7100 or DP-7110	Option: DP-7100 or DP-7110	Option: DP-7100 or DP-7110
	Duplex	Standard	Standard	Standard
	System memory	4 GB RAM, 8 GB SSD/320 GB HDD	4 GB RAM, 8 GB SSD/320 GB HDD	4 GB RAM, 8 GB SSD/320 GB HDD
Zoom	25%–400%	25%–400%	25%–400%	
Cabinet	Option: no. 76	Option: no. 76	Option: no. 76	
Print	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
Scan	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP	TCP/IP
Fax	Originals	max A3	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	1,000/2,000	1,000/2,000	1,000/2,000

A3 MULTIFUNCTIONAL SYSTEMS



		7056i	8056i
Copy	Copy speed	70 A4 / 35 A3 pages/min	80 A4 / 40 A3 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256
	Standard paper feed	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)	4,150 (2 x 500 + 2 x 1,500 + 150 sheets)
	Optional paper feed	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible	2 x 500, 2 x 1,500, 3,000 sheets, different combinations possible
	Paper capacity, max	7,650 sheets	7,650 sheets
	Paper format	A6R–A3+	A6R–A3+
	Original feeder	Standard	Standard
	Duplex	Standard	Standard
	System memory	4.5 GB RAM, 8 GB SSD/320 GB HDD	4.5 GB RAM, 8 GB SSD/320 GB HDD
	Zoom	25%–400%	25%–400%
Cabinet	--	--	
Print	Type	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.8
	Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), XPS, PRESCRIBE IIe
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
Scan	Scan type	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP	TCP/IP
Fax	Originals	max A3	max A3
	Modem speed	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	1,000/2,000	1,000/2,000

A4 MULTIFUNCTIONAL SYSTEMS



		P-3521 MFP	P-3527w MFP
Copy	Copy speed	35 A4 pages/min	35 A4 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256
	Standard paper feed	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	Optional paper feed	2 x 250 sheets	2 x 250 sheets
	Paper capacity, max	850 sheets	850 sheets
	Paper format	A6R-A4	A6R-A4
	Original feeder	Standard	Standard
	Duplex	Standard	Standard
	System memory	512 MB RAM (max 1,536 MB RAM)	512 MB RAM (max 1,536 MB RAM)
Zoom	25%–400%	25%–400%	
Cabinet	Option: no. 78	Option: no. 78	
Print	Type	Integrated within the system	Integrated within the system
	Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2
Scan	Scan type	CIS colour and b/w	CIS colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP
Fax	Originals	--	max A4
	Modem speed	--	33.6 kbps
	Compression method	--	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	100/200

A4 MULTIFUNCTIONAL SYSTEMS



		P-4020 MFP	P-4025w MFP	P-4026iw MFP
Copy	Copy speed	40 A4 pages/min	40 A4 pages/min	40 A4 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256
	Standard paper feed	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)	350 (1 x 250 + 100 sheets)
	Optional paper feed	2 x 250 sheets	2 x 250 sheets	2 x 250 sheets
	Paper capacity, max	850 sheets	850 sheets	850 sheets
	Paper format	A6R-A4	A6R-A4	A6R-A4
	Original feeder	Standard (Duplex Scan)	Standard (Duplex Scan)	Standard (Duplex Scan)
	Duplex	Standard	Standard	Standard
	System memory	512 MB RAM (max 1,536 MB RAM)	512 MB RAM (max 1,536 MB RAM)	512 MB RAM (max 1,536 MB RAM)
Zoom	25%–400%	25%–400%	25%–400%	
Cabinet	Option: no. 78	Option: no. 78	Option: no. 78	
Print	Type	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2/2016, Linux, Mac ex OS 10.6
	Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2	Windows XP, Vista, Windows 7/8/8.1/10, Server 2003/2008 R2/2012 R2
Scan	Scan type	CIS colour and b/w	CIS colour and b/w	CIS colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP
Fax	Originals	--	max A4	max A4
	Modem speed	--	33.6 kbps	33.6 kbps
	Compression method	--	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	100/200	100/200

A4 MULTIFUNCTIONAL SYSTEMS



		P-4531 MFP	P-4536 MFP	P-4531i MFP	P-4536i MFP
Copy	Copy speed	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min	45 A4 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256	256	256
	Standard paper feed	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	Optional paper feed	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets	4 x 500 sheets
	Paper capacity, max	2,600 sheets	2,600 sheets	2,600 sheets	2,600 sheets
	Paper format	A6R-A4	A6R-A4	A6R-A4	A6R-A4
	Original feeder	Standard	Standard	Standard	Standard
	Duplex	Standard	Standard	Standard	Standard
	System memory	1 GB RAM, (max 3 GB RAM), 32/128 GB SSD	1 GB RAM, (max 3 GB RAM), 32/128 GB SSD	1 GB RAM, (max 3 GB RAM), 32/128 GB SSD	1 GB RAM, (max 3 GB RAM), 32/128 GB SSD
Zoom	25%–400%	25%–400%	25%–400%	25%–400%	
Cabinet	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	
Print	Type	Integrated within the system	Integrated within the system	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
Scan	Scan type	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP	TCP/IP	TCP/IP
Fax	Originals	--	max A4	--	max A4
	Modem speed	--	33.6 kbps	--	33.6 kbps
	Compression method	--	JBIG, MMR, MR, MH	--	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	--	22/100	--	100/200

A4 MULTIFUNCTIONAL SYSTEMS



		P-5536i MFP	P-6036i MFP
Copy	Copy speed	55 A4 pages/min	60 A4 pages/min
	Copy resolution	600 x 600 dpi	600 x 600 dpi
	Greyscales	256	256
	Standard paper feed	600 (1 x 500 + 100 sheets)	600 (1 x 500 + 100 sheets)
	Optional paper feed	4 x 500 sheets	4 x 500 sheets
	Paper capacity, max	2,600 sheets	2,600 sheets
	Paper format	A6R-A4	A6R-A4
	Original feeder	Standard (Duplex Scan)	Standard (Duplex Scan)
	Duplex	Standard	Standard
	System memory	1 GB RAM (max 3 GB RAM), 32/128 GB SSD	1 GB RAM (max 3 GB RAM), 32/128 GB SSD
Zoom	25%–400%	25%–400%	
Cabinet	Option: high no. 79, low no. 80	Option: high no. 79, low no. 80	
Print	Type	Integrated within the system	Integrated within the system
	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host	USB 2.0, 10/100/1000BaseTX, USB host
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016, Novell NetWare, Linux, Mac ex OS 10.5
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter X24E, Epson LQ-850, PDF 1.7, XPS	
Network	Interfaces	10/100/1000BaseTX	10/100/1000BaseTX
	Network protocols	TCP/IP, Net BEUI	TCP/IP, Net BEUI
	Operating systems	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016	Windows 7/8/8.1/10, Server 2008/2008 R2/2012/2012 R2/2016
Scan	Scan type	CCD colour and b/w	CCD colour and b/w
	Scan resolution	200, 300, 400, 600 dpi	200, 300, 400, 600 dpi
	Interfaces	10/100/1000BaseTX, USB 2.0	10/100/1000BaseTX, USB 2.0
	Network protocols	TCP/IP	TCP/IP
Fax	Originals	max A4	max A4
	Modem speed	33.6 kbps	33.6 kbps
	Compression method	JBIG, MMR, MR, MH	JBIG, MMR, MR, MH
	One-touch dial/abbr. dial	100/200	100/200

A3 PRINT SYSTEMS



LP 4151

Print format	A6R-A3
Print speed	51 A4 / 26 A3 pages/min
Print resolution	1,200 x 1,200 dpi
Standard paper feed	1,200 (2 x 500 + 200 sheets)
Optional paper feed	2 x 500, 3,000 sheets
Duplex	Standard
Processor	PowerPC 750FL/600 MHz
Print memory	128 MB (max 640 MB)
Interfaces	IEEE 1284 parallel, USB 2.0, 10/100BaseTX, CF slot
Interfaces optional	--
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), Line Printer, Diablo 630, Epson LQ-850, IBM Proprinter X24E, KCGI, PRESCRIBE IIe

A4 PRINT SYSTEMS



P-3522DW

Print format	A6R-A4
Print speed	35 A4 pages/min
Print resolution	600 x 600 dpi, 1,200 x 1,200 dpi
Standard paper feed	350 (250 + 100 sheets)
Optional paper feed	2 x 250 sheets
Duplex	Standard
Processor	Cortex-A9 / 800 MHz
Print memory	256 MB (max 256 MB)
Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
Interfaces optional	--
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



P-4020DN

Print format	A6R-A4
Print speed	40 A4 pages/min
Print resolution	600 x 600 dpi, 1,200 x 1,200 dpi
Standard paper feed	350 (250 + 100 sheets)
Optional paper feed	2 x 250 sheets
Duplex	Standard
Processor	Cortex-A9 / 800 MHz
Print memory	256 MB (max 256 MB)
Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot
Interfaces optional	--
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS

P-4020DW

Print format	A6R-A4
Print speed	40 A4 pages/min
Print resolution	600 x 600 dpi, 1,200 x 1,200 dpi
Standard paper feed	350 (250 + 100 sheets)
Optional paper feed	2 x 250 sheets
Duplex	Standard
Processor	Cortex-A9 / 800 MHz
Print memory	256 MB (max 256 MB)
Interfaces	10/100/1000BaseTX, USB 2.0, USB host, SD slot, Wi-Fi
Interfaces optional	--
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, Epson LQ-850, PDF 1.7, XPS, Open XPS



P-4531DN

Print format	A6R-A4
Print speed	45 A4 pages/min
Print resolution	1,200 x 1,200 dpi
Standard paper feed	600 (500 + 100 sheets)
Optional paper feed	4 x 500 sheets
Duplex	Standard
Processor	Cortex-A9 / 1,200 MHz
Print memory	512 MB (max 2 GB)
Interfaces	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
Interfaces optional	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS



P-5031DN

Print format	A6R-A4
Print speed	50 A4 pages/min
Print resolution	1,200 x 1,200 dpi
Standard paper feed	600 (500 + 100 sheets)
Optional paper feed	4 x 500 sheets
Duplex	Standard
Processor	Cortex-A9 / 1,200 MHz
Print memory	512 MB (max 2 GB)
Interfaces	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
Interfaces optional	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS

P-5531DN

Print format	A6R-A4
Print speed	55 A4 pages/min
Print resolution	1,200 x 1,200 dpi
Standard paper feed	600 (500 + 100 sheets)
Optional paper feed	4 x 500 sheets
Duplex	Standard
Processor	Cortex-A9 / 1,200 MHz
Print memory	512 MB (max 2 GB)
Interfaces	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
Interfaces optional	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS

P-6031DN

Print format	A6R-A4
Print speed	60 A4 pages/min
Print resolution	1,200 x 1,200 dpi
Standard paper feed	600 (500 + 100 sheets)
Optional paper feed	4 x 500 sheets
Duplex	Standard
Processor	Cortex-A9 / 1,200 MHz
Print memory	512 MB (max 2 GB)
Interfaces	10/100/1000BaseTX, USB 2.0, USB host (2), SD slot
Interfaces optional	IEEE 1284 parallel, 10/100/1000BaseTX, WLAN card
Emulations	PCL6 (5e, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIe, Line Printer, IBM Proprinter, XPS, Open XPS

www.triumph-adler.com

We develop **individual processes in the fields of document solutions, information and IT.** Document technology is our core business and we continuously develop our portfolio. At the same time, we assist our customers in creating flexible and modern workplaces with our pioneering mobile solutions and cloud services. Efficient processes are crucial for the success of a company. **We can assist you with solutions for saving time and money with your workflows** and support you with our expertise in implementing professional hardware and software solutions.

TA Triumph-Adler